

## Three Chamber Organic Septic Tanks

### 1 Dimensions

TYPE	A.E	EFFECTIVE VOLUME	EXTERNAL DIMENSIONS			SEPTIC TANK (A)	PEDESTRIAN COVER 200 kg/m <sup>2</sup>		(A) + (B)	LIGHT TRAFFIC COVER 2000 kg/m <sup>2</sup>		(A) + (C)	HEAVY TRAFFIC COVER 7000 kg/m <sup>2</sup>		(A) + (D)
			Width cm	Length cm	Height cm		Weight 100 kg	Thickness cm		Weight 100 kg	Weight 100 kg		Thickness cm	Weight 100 kg	
Code	no.	septic tanks 150 l/inhab.	Width cm	Length cm	Height cm	Weight 100 kg	Thickness cm	Weight 100 kg	Weight 100 kg	Thickness cm	Weight 100 kg	Weight 100 kg	Thickness cm	Weight 100 kg	Weight 100 kg
SET-0*	20-25	4.000	160	250	170	60	10	9	69	16	14	74	20	18	78
SET-01*	30-33	5.000	160	250	200	66	10	9	75	16	14	80	20	18	84
SET-02*	40	6.000	160	290	200	70	10	10	80	16	17	87	20	20	90
SET-03*	42	6.400	200	250	200	74	10	11	85	16	19	93	20	22	96
SET-04*	43	6.500	160	250	250	80	10	9	89	16	14	94	20	18	98
SET-05*	50	7.700	160	290	250	85	10	10	95	16	17	102	20	20	105
SET-06	54	8.100	250	250	200	86	10	14	100	16	24	110	20	28	114
SET-07	55	8.250	200	250	250	90	10	11	101	16	19	109	20	22	112
SET-08	70	10.500	250	250	250	102	10	14	116	16	24	126	20	28	130
SET-09	73	10.950	250	325	200	104	10	19	123	16	31	135	20	38	142
SET-10	92	13.800	250	400	200	126	10	24	150	16	38	164	20	46	172
SET-11	95	14.250	250	325	250	122	10	19	141	16	31	153	20	38	160
SET-12	104	15.700	250	450	200	133	10	26	159	16	43	176	20	52	185
SET-13	120	18.000	250	400	250	141	10	24	165	16	38	179	20	46	187
SET-14	130	19.500	250	550	200	154	10	32	186	16	52	206	20	64	218
SET-15	136	20.400	250	450	250	155	10	26	171	16	43	198	20	46	201
SET-16	155	23.250	250	650	200	174	10	38	212	16	62	236	20	76	250
SET-17	170	25.500	250	550	250	177	10	32	209	16	52	229	20	64	241
SET-18	180	27.000	250	750	200	200	10	44	244	16	72	272	20	88	288
SET-19	200	30.000	250	650	250	200	10	38	238	16	62	262	20	76	276
SET-20	230	34.500	250	950	200	239	10	56	295	16	92	331	20	114	353
SET-21	235	35.300	250	750	250	232	10	44	276	16	72	304	20	88	320
SET-22	246	37.000	250	1017	200	274	10	61	335	16	98	372	20	122	396
SET-23	300	45.000	250	950	250	272	10	56	328	16	92	364	20	114	386
SET-24	320	48.000	250	1017	250	300	10	61	361	16	98	398	20	122	422

\*CE marked product

Please contact our Sales Office if you require larger treatment plants.

The cast iron inspection covers on the pedestrian covers are class B125.

The cast iron inspection covers on the vehicle covers for light traffic are class C250.

The cast iron inspection covers on the vehicle covers for heavy traffic are class D400.

The foundation slab must be at least 20 cm thick and be reinforced with a double electrically welded steel mesh, 8 mm diameter, 20x20 cm mesh.

A 3-5 cm layer of sand must be laid on the foundation slab where the prefabricated elements will be placed.

**Gazebo S.p.A. Italy - 47043 Gatteo FC - via Molino Vecchio, 9 - tel. +39 0541 818060 - fax +39 0541 818542 - gazebo@gazebo.it - www.gazebo.it**

All dimensions given are indicative. Gazebo S.p.A. allows a small tolerance